

Tipo

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10 "					
Aspect	ISO 2424		Loop pile					
Dye method			Solution dyed					
Dimensions	EN 994	cm x cm	50 x 50 / 19.68" x 19.68" (20 tiles per box)					
Primary backing	ISO 2424		Polyester - polyamide fleece					
Secondary backing	ISO 2424		Modified bitumen					
Pile fibre composition	ISO 2424		Polypropylene					
Total thickness	ISO 1765	mm	6.5	inch	0.26			
Effective pile thickness	ISO 1766	mm	3.0	inch	0.12			
Total mass	ISO 8543	g/m ²	4000	oz/yd ²	118.1			
Total pile mass	ISO 2424	g/m ²	500	oz/yd ²	14.8			
Effective pile mass	ISO 8543	g/m ²	225	oz/yd ²	06.6			
Pile density	ISO 8543	g/cm ³	0.075	lb/in ³	0.0027			
Number of tufts	ISO 1763	/dm ²	1540	/yd ²	128759			
Stroll test	ISO 6356	kV	≤ 2.0					
Vertical resistance	ISO 10965	Ohm	-					
Horizontal resistance	ISO 10965	Ohm	-					
Use classification	EN 1307		22 Domestic - moderate use					
Luxury rating	EN 1307		LC 1					
Dimensional stability	EN 986	%	≤ 0.2					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
			α _s	-	-	-	-	-
Noise reduction	ISO 354	α _w	-					
Thermal resistance	ISO 8302	m ² .K/W	-					
Flammability	EN 13501-1		Dfl - s1					

EN 14041


 0

Manufactured by:

 Desso BV

 PO Box 169

 NL - 5140 AD Waalwijk



Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings.

Note: Desso reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www.desso.com